

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr

Ora

VK/02282/W/W




Glossy White. CCT 2200K/2700K/3000K. 2.2W. 140/150/160lm.
 2x2200mah lithium battery. LED lumileds 4014. AC 100-240V, DC5V 1A.
 Outdoor Portable. 120°. Charge time 4-5 hours. Work time 11-12 hours.
 With Touch switch. 0°C - 40°C. 30.000hrs. Dimmable Yes 5-100%.
 Without adapter. CRI>80. Die-casting aluminum, PC. IP65

IP65



Dimensions



Gallery





Downloads




VK Leading Light

Since 1978

Technical Specifications	
Kelvin	CCT 2200K/2700K/3000K
Power	2.2W
Voltage	AC 100-240V, DC5V 1A
Battery	2x2200mah lithium batteries
Charge	4-5 hours
Work time	11-12 hours
Extra	With touch switch
Fitting	Outdoor portable
Type	Light
Safety class	
Light source	Lumileds 4014
IP Rating	IP65
CRI	CRI>80
Dimmable	
Lifetime	30.000hrs
Clicks	25,000
Adapter	No
Working temperature	0°-40°C
PAGE	342 New Products 2026
NICKNAME	Ora

Physical Specifications	
Family	Ora
Color	Glossy white
Material	Die-casting aluminum, PC
Width	ø8cm
Length	ø8cm
Height	24.2cm
Net weight of product (kg)	0.35kg
Gross weight with inner box (kg)	0.43kg
Width (inner box)	13cm
Length (inner box)	13cm
Height (inner box)	28.5cm

Illumination Data	
Lumen	140/150/160lm
Beam angle	120°
Lighting direction	

Packing Info	
Pcs/carton	12pcs

Certification & Warranty	
Guarantee	3 years

Energy Label

